

PRODUCT INFORMATION



EUROLUB FORMEL 2 10W/40

Description/Applications:	It is designed for the lubrication of four –stroke gasoline and diesel cars, including diesel engines with direct injection. Key features include a low ash formulation and a high resistance to ageing. Ideal for most gasoline and diesel engines. Particularly recommended for Direct Injection diesel engines. Pay attention to users manual !!
----------------------------------	--

Can be used with:	ACEA A3/B4 API SL/CF
--------------------------	-------------------------

Delivery:	Art.-Nr. 237005	4 x 5 Liter	canister
	Art.-Nr. 237020	20 Liter	can
	Art.-Nr. 237060	60 Liter	hobbock
	Art.-Nr. 237208	208 Liter	drum
	Art.-Nr. 237100	1000 Liter	IBC

Technical data:

Data	Unit	Method	EUROLUB Formel 2 10W/40
Density at 15°C	kg/L	ASTM D 4052	0,860
Viscosity at 40°C	cSt	ASTM D 445	85,10
Viscosity at 100°C	cSt	ASTM D 445	13,40
Flash point (COC)	°C	ASTM D 92	>200
Pourpoint	°C	ASTM D 6892	-25

The data provided are subject to change. Operating rules of the manufacturer.

Characteristics are typical of current production data are subject to change.

This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 D-85386 Eching - Germany Tel. 0049/8165 / 95 91 - 0, Fax 0049/8165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 01.03.2016, made:01.03.2016
	reference: dynspec, 30.11.2015+20259/Spec.Kat.2016
	name: FORMEL 2 10W-40 PDS_GB.docx
	page 1 of 1