

EUROLUB

Gatteröl-Haftöl Spezial 150

Gatteröl - Haftöl Special 150 is a strong filament pulling, and adhesive lubricating oil that forms a stable and pressure resistant lubricating film. Special active ingredients give this oil optimum adhesion properties, good corrosion resistance and oxidation resistance. Due to the strong adhesion of the lubricating film is not even on vertical surfaces. Vertical guides and sliding surfaces can be lubricated properly, as the lubricating film not tear off.

Category:	Speciala - Adhesion Oil
------------------	-------------------------

Product Features:	<ul style="list-style-type: none">◆ Reliable lubrication.◆ Extended lubrication intervals.◆ No stick-slip (stick-slip phenomenon)◆ Reduced oil consumption.◆ avoidance of oil patches.
--------------------------	--

Application:	<p>Gatteröl – Haftöl Spezial 150 of all machine tools such as drilling, grinding, turning, planing and broaching machines. It prevents the dreaded stick slip the slide on the tracks this machine tool, even at very low feedrates and therefore contributes to increased working accuracy. The lubricant feed can be done by centralized lubrication systems, mechanical lubricator or by hand with oil can. Also drip and wick lubricators are suitable.</p> <p>Many production machines in the metal processing industry, packaging, rotary machines and the like have (open) sliding bearing bolts, hinges, chains, racks, sliding and column guides. For all these lubrication points, the Gatteröl - Haftöl Spezial 150 is excellent, because it neither drips nor squirt. Adhesive lubricants not crawl out of the bearings and along the waves. The oil film remains considerably longer at the lubrication point than the commercially available machine oils. The lubrication intervals can be substantially extended, the oil consumption is reduced.</p>
---------------------	---

Can be used with:	ISO-VG 150
--------------------------	------------

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 - 0, Fax 08165 / 95 91 - 20 www.eurolub.de , info@eurolub.de	Druckdatum: 12.10.2015, erstellt am 05:03:2014/HB
	Autor: MS
	Name: Gatteröl-Haftöl Spezial 150 PDS_GB
	Seite 1 von 2

PRODUCT INFORMATION



Delivery:	Art.-Nr. 351020	20 Liter	plastic canister
	Art.-Nr. 351060	60 Liter	hobbock
	Art.-Nr. 351208	208 Liter	drum
	Art.-Nr. 351100	Container	800 – 3.000 Liter per destination

Technical Data

Data	Unit	Method	EUROLUB Gatteröl- Haftöl Spezial 150
Density at 15°C	g/cm ³	DIN 51 757	0,886
Viscosity at 40°C	mm ² /s	DIN 51 562	149,20
Viscosity at 100°C	mm ² /s	DIN 51 562	14,90
Flash point (COC)	°C	DIN ISO 2592	241
Pourpoint	°C	DIN ISO 3016	-11

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.