

# PRODUCT INFORMATION



## EUROLUB Kühlerschutz ANF

Kühlerschutz ANF is a nitrite, amine and phosphate free antifreeze based on ethylene glycol (MEG mono ethylene glycol ethanediol). Suitable for summer and winter with rust and frost protection. .  
Kühlerschutz ANF must be diluted with water before use.

<b>Description/Applications:</b>	<p>Kühlerschutz ANF protects against corrosion, cavitation and deposits. It reduced foam. Not used in conjunction with galvanized pipes or containers</p> <p>Kühlerschutz ANF is distinguished by its special corrosion protection additives for gray cast iron or aluminum motors suitable not foam and behaves neutrally to metals, rubber parts and seals.</p> <p>Kühlerschutz ANF increases the boiling point and reduces the freezing point of the coolant (antifreeze coolant = + water). Kühlerschutz ANF is applied with a recommended concentration of use of 50%, with a frost protection of -37 ° C is reached.</p>
----------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>Can be used with:</b>	BS 6580
--------------------------	---------

<b>Delivery:</b>	Art.-Nr. 820015	12 x 1,5 Liter	bottle
	Art.-Nr. 820005	4 x 5 Liter	can
	Art.-Nr. 820020	20 Liter	canister
	Art.-Nr. 820060	60 Liter	hobbock
	Art.-Nr. 820208	208 Liter	drum
	Art.-Nr. 820100	Container	IBC 1.000L

# PRODUCT INFORMATION



## Water mixtures:

(Do not mix below -20 ° C, since less than 33% Antifreeze no corrosion protection is guaranteed.)

Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer.

Characteristics are typical of current production data are subject to change.

This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.