

EUROLUB SUPER ECO 0W/16

Description/Applications:	<p>A fuel economy SAE 0W16 motor oil, developed according the most recent technology, based on specially selected base oils and a well balanced choice of advanced additives to obtain the following properties:</p> <ul style="list-style-type: none"> - a lower fuel consumption - a high and stable viscosity index - a good resistance against shearing <p>This fuel economy, specially composed SAE 0W16 motor oil, is recommended for use in petrol engines in passenger cars of Japanese OEMs, equipped with the latest techniques.</p>
----------------------------------	---

Can be used with:	API SN
--------------------------	--------

Delivery:	Art.-Nr. 222001	12 x 1 Liter	bottle
	Art.-Nr. 222020	20 Liter	can
	Art.-Nr. 222060	60 Liter	hobbock
	Art.-Nr. 222208	208 Liter	drum
	Art.-Nr. 222100	1000 Liter	IBC

Technical Data:			
Data	Unit	Method	EUROLUB SUPER ECO 0W/16
Density at 15°C	kg/L	ASTM D 4052	0,846
Viscosity at 40°C	cSt	ASTM D 445	37,90
Viscosity at 100°C	cSt	ASTM D 445	7,10
Viscosityindex (VI)		ASTM D 2270	153
Flash point (COC)	°C	ASTM D 92	>200
Pourpoint	°C	ASTM D 6892	-38

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.