## PRODUCT INFORMATION



## **EUROLUB Multitec 5W-30**

## **Description Applications:**

This fuel economy motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below. This motor oil is specially developed for those cars, that ask for motor oils that fulfill the recent requirements of the OEM's. This oil is fully backwards compatible with Ford M2C 913-A, B and C.

Can be used with:	ACEA A5/B5
	API SL/CF
	Ford WSS-M2C913-D (covers 913-A/-B/-C)
	Renault RN0700
	Jaguar Land Rover STJLR.03.5003

Delivery:	ArtNr. 214001	12 x 1 Liter	bottle
	ArtNr. 214004	4 x 4 Liter	can
	ArtNr. 214005	4 x 5 Liter	can
	ArtNr. 214020	20 Liter	can
	ArtNr. 214060	60 Liter	hobbock
	ArtNr. 214208	208 Liter	drum
	ArtNr. 214100	Container	IBC

Technical Data:				
Data	Unit	Method	EUROLUB MULTITEC 5W-30	
Density at 15°C	kg/L	D 4052	0,849	
Viscosity at 40°C	cSt	D 445	59	
Viscosity at 100°C	cSt	D 445	10,2	
Viscosityindex (VI)		D 2270	163	
Flash point (COC)	°C	D 92	234	
Pourpoint	°C	D 6892	-33	

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH	print: 25.08.2020, made 18.04.2018
Freisinger Strasse 25-27 85386 Eching / Germany	Referenz: R20366, 25.07.2019
Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20	Name: 214xxx_TDS_EN
www.eurolub.com, info@eurolub.com	Seite 1 von 1