

EUROLUB CLEANSTAR C2 5W-30

Description/Applications:	This universal, fuel economy, low SAPS motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters. The operating instructions of the vehicle and engine manufactures must be followed.
----------------------------------	---

Can be used with:	ACEA C2 API SN/CF PSA B71 2290 Renault RN 0700 Fiat 9.55535-S1
--------------------------	--

Delivery:	Art.-Nr. 223001	12 x 1 Liter	bottle
	Art.-Nr. 223005	4 x 5 Liter	can
	Art.-Nr. 223020	20 Liter	can
	Art.-Nr. 223060	60 Liter	hobbock
	Art.-Nr. 223208	208 Liter	drum
	Art.-Nr. 223100	Container	IBC

Technical Data:			
Data	Unit	Method	EUROLUB CLEANSTAR C2 5W-30
Density at 15°C	kg/L	D 4052	0,853
Viscosity at 40°C	cSt	D 445	58,0
Viscosity at 100°C	cSt	D 445	10,2
Viscosityindex (VI)		D 2270	162
Flash point (COC)	°C	D 92	235
Pourpoint	°C	D 6892	-33

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 10.09.2019, made: 20.11.2018
	Referenz: R20363, 25.07.2019
	Name: 223xxx_TDS_EN
	Seite 1 von 1