

## EUROLUB MOTOR VO 0W-30



<b>Description/Applications:</b>	<p>This modern synthetic fuel economy motor oil is produced with special selected synthetic base oils and a well-balanced choice of advanced additives to obtain the following properties:</p> <ul style="list-style-type: none"> <li>- a lower fuel consumption</li> <li>- a high and stable viscosity index</li> <li>- a high resistance against shearing</li> <li>- a very fast cold start</li> <li>- a safe lubrication film at high temperatures</li> <li>- a very good detergency and dispersion power</li> <li>- a very strong protection against wear, corrosion and foaming</li> </ul>
----------------------------------	---

<b>Can be used with:</b>	<p>ACEA A5 / B5 API SL Meets the requirements of Volvo VCC 95200377</p>
--------------------------	---

<b>Delivery:</b>	<table> <tr> <td>Art.-Nr. 243001</td> <td>12 x 1 Liter</td> <td>bottle</td> </tr> <tr> <td>Art.-Nr. 243005</td> <td>4 x 5 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 243020</td> <td>20 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 243060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 243208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 243100</td> <td>Container</td> <td>IBC</td> </tr> <tr> <td>Art.-Nr. 243000</td> <td>Bulk</td> <td></td> </tr> </table>	Art.-Nr. 243001	12 x 1 Liter	bottle	Art.-Nr. 243005	4 x 5 Liter	can	Art.-Nr. 243020	20 Liter	can	Art.-Nr. 243060	60 Liter	hobbock	Art.-Nr. 243208	208 Liter	drum	Art.-Nr. 243100	Container	IBC	Art.-Nr. 243000	Bulk	
Art.-Nr. 243001	12 x 1 Liter	bottle																				
Art.-Nr. 243005	4 x 5 Liter	can																				
Art.-Nr. 243020	20 Liter	can																				
Art.-Nr. 243060	60 Liter	hobbock																				
Art.-Nr. 243208	208 Liter	drum																				
Art.-Nr. 243100	Container	IBC																				
Art.-Nr. 243000	Bulk																					

<b>Technical Data:</b>			
<b>Data</b>	<b>Unit</b>	<b>Method</b>	<b>EUROLUB Motor VO 0W-30</b>
Density at 15°C	kg/L	D 4052	0,850
Viscosity at 40°C	cSt	D 445	53,5
Viscosity at 100°C	cSt	D 445	10,1
Viscosityindex (VI)		D 2270	178
Flash point (COC)	°C	D 92	210
Pourpoint	°C	D 6892	-43

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	print: 24.08.2020, made 18.09.2017
	Referenz: R20349, 21.10.2019
	Name: 243xxx_TDS_EN
	Seite 1 von 1