## PRODUCT INFORMATION



## EUROLUB 2 TZ RACING

Description /	2 TZ RACING is a self-mixing two-stroke engine oil.		
Applications:	The technical requirements, that is ensuring piston cleanliness and		
	corrosion protection and the prevention of ring sticking, galling and glow		
	ignition, are met by the use of synthetic components with significant		
	reserve.		
	2 TZ RACING is recommended self-mixing according to the manufacturer's		
	instructions for mixing ratios up to 1:100. It is also suitable for use in oil		

injection (autolube systems).

Can be used with:	API TC
	Jaso FD
	ISO-L-EGD
	Global GD
	Husqvarna 272
	2-Stroke DFI

Delivery:	ArtNr. 303001	12 x 1 Liter	bottle
	ArtNr. 303020	20 Liter	can
	ArtNr. 303060	60 Liter	hobbock
	ArtNr. 303208	208 Liter	drum
	ArtNr. 303100	Container	IBC

Technical Data:					
Data	Unit	Method	EUROLUB 2TZ RACING		
Density at 15°C	kg/L	D 4052	0,870		
Viscosity at 40°C	cSt	D 445	64,6		
Viscosity at 100°C	cSt	D 445	9,5		
Viscosityindex (VI)		D 2270	129		
Flash point (COC)	°C	D 92	116		
Pourpoint	°C	D 6892	-24		

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

 EUROLUB GmbH
 print: 24.08.2020, made 20.11.2018

 Freisinger Strasse 25-27
 Referenz: STA1302, 02.08.2018

 85386 Eching / Germany
 Name: 303xxx\_TDS\_EN

 Tel. +49 8165 9591 - 0, Fax +49 8165 9591 - 20
 Seite 1 von 1