

EUROLUB 4TZ PREMIUM 10W-40

| | |
|----------------------------------|--|
| Description/Applications: | <p>High-performance engine oil with base oils. Developed specifically for use in 4-stroke motorcycles with wet-running oil bath clutches.</p> <p>Its exceptionally high level of performance is achieved through the interaction of this special base oil composition and the advanced additives.</p> <ul style="list-style-type: none"> • Excellent clutch performance; meets the stringent JASO MA2 requirements. • High level of oxidation protection by means of selected base oils and special additives. |
|----------------------------------|--|

| | |
|--------------------------|-----------------------------|
| Can be used with: | JASO MA2 API SL/SJ/SH/SG |
|--------------------------|-----------------------------|

| | | | |
|------------------|-----------------|--------------|---------|
| Delivery: | Art.-Nr. 313001 | 12 x 1 Liter | bottle |
| | Art.-Nr. 313020 | 20 Liter | can |
| | Art.-Nr. 313060 | 60 Liter | hobbock |
| | Art.-Nr. 313208 | 208 Liter | drum |
| | Art.-Nr. 313100 | Container | IBC |

Technical Data:

| Data | Unit | Method | EUROLUB 4TZ PREMIUM 10W-40 |
|---------------------|------|--------------|-------------------------------|
| Density at 15°C | kg/L | ASTM D 7042 | 0,867 |
| Viscosity at 40°C | cSt | ASTM D 7042 | 98,0 |
| Viscosity at 100°C | cSt | ASTM D 7042 | 14,4 |
| Viscosityindex (VI) | | ASTM D 7042 | 154 |
| Flash point (COC) | °C | DIN ISO 2592 | 226 |
| Pourpoint | °C | DIN ISO 3016 | -30 |

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.