

EUROLUB MULTICARGO 10W-40

Description/Applications:	MULTICARGO 10W-40 is a Ultra-High-Performance-Diesel motor oil. This product has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for Euro 4 and Euro 5 engines without particelfilter and for the most engines with exhaustgasemission systems. The operating instructions of the vehicle and engine manufactures must be followed.
----------------------------------	---

Can be used with:	ACEA E7 API CI-4 MB 228.5 Volvo VDS-3 Renault VI RXD/RLD-2 Deutz IV-10 Cummins CES 20078	MAN M 3377 / 3277 Global DHD-1 MTU Type 3 Mack EO-N / EO-M plus Detroit Diesel 93K215
--------------------------	--	---

Delivery:	Art.-Nr. 318020	20 Liter	can
	Art.-Nr. 318060	60 Liter	hobbock
	Art.-Nr. 318208	208 Liter	drum
	Art.-Nr. 318100	Container	IBC

Technical Data:			
Data	Unit	Method	EUROLUB MULTICARGO 10W-40
Density at 15°C	kg/L	D 4052	0,855
Viscosity at 40°C	cSt	D 445	97,5
Viscosity at 100°C	cSt	D 445	14,8
Viscosityindex (VI)		D 2270	155
Flash point (COC)	°C	D 92	220
Pourpoint	°C	D 6892	-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 24.08.2020, made 26.04.2018
	Referenz: R20361, 25.07.2019
	Name: 318xxx_TDS_EN
	Seite 1 von 1