## PRODUCT INFORMATION



## EUROLUB UNI TRUCK STOU 10W-30

## Description / Applications:

An up-to-date multifunctional oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined and base oils and additives, to achieve the following properties: - a powerful dispersion and detergency - a high activity against wear, corrosion and foam - a very strong resistance to oxidation - an excellent extreme pressure properties - a high and stable viscosity index

This multifunctional lubricant (\*) has been developed to achieve one single lubricating oil that is able to lubricate: - gasoline engines - diesel engines (with or without turbo-charging) - transmissions (also "wet" brakes) - hydraulic systems (\*) a so-called Super Tractor Oil Universal=STOU

Can be used with: API SF/CG-4/GL-4

Allison C-4 NH 410B / NH030C / 82009201

Cat TO-2 John Deere J27 / J27C
Ford M2C159-B/C Ford M2C86-B / M2C134-D

Massey Ferguson M1145/M1144/M1139/M1135

ZF TE-ML 03A/05K/06B/06C/07B/07D

Delivery:	ArtNr. 322020	20 Liter	canister
	ArtNr. 322060	60 Liter	hobbock
	ArtNr. 322208	208 Liter	drum
	ArtNr. 322100	Container	IBC 1.000L

Technical Data:				
Data	Unit	Method	EUROLUB UNI TRUCK STOU 10W-30	
Density at 15°C	kg/L	ASTM D 4052	0,873	
Viscosity at 40°C	cSt	ASTM D 445	68,7	
Viscosity at 100°C	cSt	ASTM D 445	10,5	
Viscosityindex (VI)		ASTM D 2270	139	
Flash point (COC)	°C	ASTM D 92	220	
Pourpoint	°C	ASTM D 6892	-48	

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

 EUROLUB GmbH
 Druckdatum: 25.08.2020, erstellt am 20.11.2018

 Freisinger Strasse 25-27
 Referenz: 150094PE, 01.10.2017

 85386 Eching bei München
 Name: 322xxx\_TDS\_EN

 Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20
 Seite 1 von 1