

EUROLUB UNI TRUCK STOU 15W-30

Description / Applications:

An up-to-date multifunctional oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined and base oils and additives, to achieve the following properties: - a powerful dispersion and detergency - a high activity against wear, corrosion and foam - a very strong resistance to oxidation - an excellent extreme pressure properties - a high and stable viscosity index

This multifunctional lubricant (*) has been developed to achieve one single lubricating oil that is able to lubricate: - gasoline engines - diesel engines (with or without turbo-charging) - transmissions (also "wet" brakes) - hydraulic systems (*) a so-called Super Tractor Oil Universal=STOU

Can be used with:

API SF/CG-4/GL-4	NH 410A / NH 82009202
Allison C-4	John Deere J27
Ford M2C159-B/C	Cat TO-2
Ford M2C134-A	
Massey Ferguson CMS M1145 / M1144 / M1139 / M 1135	
Eaton M29505, I-280-S	
ZF TE-ML 06B/06C/07B/07D	

Delivery:

Art.-Nr. 324020	20 Liter	canister
Art.-Nr. 324060	60 Liter	hobbock
Art.-Nr. 324208	208 Liter	drum
Art.-Nr. 324100	Container	IBC 1.000L

Technical Data:

Data	Unit	Method	EUROLUB UNI TRUCK STOU 15W-30
Density at 15°C	kg/L	ASTM D 4052	0,869
Viscosity at 40°C	cSt	ASTM D 445	67,5
Viscosity at 100°C	cSt	ASTM D 445	10,0
Viscosityindex (VI)		ASTM D 2270	134
Flash point (COC)	°C	ASTM D 92	220
Pourpoint	°C	ASTM D 6892	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print 24.08.2020, made 20.11.2018
	Referenz: 150096PE,01.2017
	Name: 324xxx_TDS_EN
	Seite 1 von 1