

EUROLUB HD 4C 20W-20

Description/Applications:	<p>4C HD 20W-20 is a universally usable high-performance monograde oil.</p> <p>The range of services covers the requirements of Diesel engines with and without turbocharging, as well as 4C HD 20W-20 is suitable for use in commercial vehicle diesel engines of fleets, agricultural and construction aggregates. It can be used in hydraulic clutches, transmissions, converter gear transmissions and retarders as hydraulic oil.</p>
----------------------------------	--

Can be used with:	<p>API CD/SF Caterpillar Series 3 David Brown DB OM 616 MACK EO-J MIL-L 2104 C Volvo B20</p>
--------------------------	--

Delivery:	Art.-Nr. 332020	20 Liter	canister
	Art.-Nr. 332060	60 Liter	hobbock
	Art.-Nr. 332208	208 Liter	drum
	Art.-Nr. 332100	Container	800 – 3.000 Liter per destination

Technical data:			
Data	Unit	Method	EUROLUB HD 4C 20W-20
Density at 15°C	kg/l	DIN EN ISO 12185	0,872
Viscosity at 40°C	mm ² /s	DIN 51 562-1	56,7
Viscosity at 100°C	mm ² /s	DIN 51 562-1	8,43
Viscosity Index (VI)		DIN ISO 2909	115
Flashpoint COC	°C	DIN ISO 2592	220
Pourpoint	°C	DIN ISO 3016	-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.de , info@eurolub.de	print 24.08.2020, made 20.11.2018
	Referenz: MN3102, 01.09.2019
	Name: 332xxx_TDS_ENDS(GB)
	Seite 1 von 1