

## EUROLUB GEAR SYNT 75W-90

<b>Description/Applications:</b>	<p>This gear oil is a lubricating oil for mechanical transmissions, formulated with high quality special refined and base oils and special EP-additives to obtain the following properties:</p> <ul style="list-style-type: none"> <li>- excellent resistance against oxidation</li> <li>- a very high activity against wear, corrosion and foam</li> <li>- a low pour point</li> <li>- very good EP-properties</li> <li>- fuel economy</li> </ul>
----------------------------------	--

<b>Can be used with:</b>	<p>API GL-4/5 MIL-L-2105 D MAN 341 Typ Z2 MAN 342 Typ M2 MB 235.0 / 235.1 ZF TE-ML 05A/07A/12E/16B/16C/17B/19B</p>
	<p>BMW 83 22 9 407 768 Ford 1 347 488 GM 93165290 Opel 19 40 182 Vauxhall 93165290 VW G 052 145 A1</p>

<b>Delivery:</b>	Art.-Nr. 374020	20 Liter	can
	Art.-Nr. 374060	60 Liter	hobbock
	Art.-Nr. 374208	208 Liter	drum
	Art.-Nr. 374100	1000 Liter	IBC

# PRODUCT INFORMATION



## Technical Data:

Data	Unit	Method	EUROLUB GEAR SYNT 75W-90
Density at 15°C	kg/L	ASTM D 4052	0,864
Viscosity at 40°C	cSt	ASTM D 445	88,0
Viscosity at 100°C	cSt	ASTM D 445	15,5
Viscosityindex (VI)		ASTM D 2270	184
Flash point (COC)	°C	ASTM D 92	180
Pourpoint	°C	ASTM D 6892	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.