

## EUROLUB GEAR LSL 75W-90

<b>Description/Applications:</b>	High-performance gearbox oil for manual gearboxes and axle gears with LS differentials (Limited Slip). It is used for conventional manual gearboxes and axle gears as a multi-functional gearbox oil in passenger cars, heavy-goods vehicles, off-road vehicles and work machines. It can also be used in axle gears with multi-disc locking differentials due to its special additive composition. The operating instructions of the vehicle and engine manufactures must be followed.
----------------------------------	--

<b>Can be used with:</b>	API GL-4 / GL-5 / GL-5 LS (Limited Slip) MAN 342 Typ M1/M2/M3 MACK GO-J/GO-J Plus Scania STO 1:0
	BMW 83 22 9 407 768 Ford 1 347 488 GM 93165290 Opel 19 40 182 Vauxhall 93165290 VW G 052 145 A1

<b>Delivery:</b>	Art.-Nr. 383001	12 x 1 Liter	bottle
	Art.-Nr. 383020	20 Liter	can
	Art.-Nr. 383060	60 Liter	hobbock
	Art.-Nr. 383208	208 Liter	drum
	Art.-Nr. 383100	1000 Liter	IBC

<b>Technical Data:</b>			
<b>Data</b>	<b>Unit</b>	<b>Method</b>	<b>EUROLUB GEAR LSL 75W-90</b>
Density at 15°C	kg/L	ASTM D 4052	0,879
Viscosity at 40°C	cSt	ASTM D 445	83,0
Viscosity at 100°C	cSt	ASTM D 445	14,8
Viscosityindex (VI)		ASTM D 2270	188
Flash point (COC)	°C	ASTM D 92	180
Pourpoint	°C	ASTM D 6892	-39

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	print: 22.09.2020, made 28.09.2017
	Referenz: MN8103, 01.09.2019
	Name: 383xxx_TDS_EN
	Seite 1 von 1