

EUROLUB HVLP-D 46

Category: HVLPD Hydraulic Fluids

**Product Features:
application:** The HVLP-D hydraulic oils is based on paraffinic base oil and modern additive technology. Effective zinc containing components guarantee optimal lubrication and long term protection against oxidation. During the process fine filtration is possible without the risk of losing valuable ingredients. High shear stability represents permanent optimal viscosity at low temperatures as well as at high operating temperatures. Dispersant and detergent additives provide optimal dirt-removing properties and the product is especially suitable for centrally supplied machines.

Recommendations: DIN 51 524 / part 3 FZG-Test A8, 3/90 load stage: >12
High shear stability (viscosity drop 20h KRL: <20%)

Delivery:

Art.-Nr. 529020 20 Liter	plastic-canister
Art.-Nr. 529060 60 Liter	hobbock
Art.-Nr. 529208 208 Liter	Drum
Art.-Nr. 529100 Container	800 – 3.000 Liter per destination

Technical Data:

Data	Unit	Method	EUROLUB HVLP-D 46
Density at 15°C	kg/L	ASTM D 4052	0,874
Viscosity at 40°C	cSt	ASTM D 445	45,6
Viscosity at 100°C	cSt	ASTM D 445	8,11
Viscosityindex (VI)		ASTM D 2270	152
Flash point (COC)	°C	ASTM D 92	228
Pourpoint	°C	ASTM D 6892	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.de , info@eurolub.de	print: 24.08.2020, made 06.06.2017
	Referenz: SwioHVG, 01.01.2016
	Name: 529xxx_TDS_EN
	Seite 1 von 1